

SUPPLIER MATERIAL SAFETY DATA SHEET (MSDS)

N/D=Not Determined
N/A=Not Applicable

Product: FRESH SCENT WAFERS

Manufacturer: ESTEAM

Flammability: 2

Chem. Name: N/A

Trade Name: Fresh Scent wafer

Reactivity: 0

Chem. Family: Mixture

Use: Wick type air freshener

Health: 1

Protection:

NFPA LEAST=0, SLIGHT=1, MODERATE=2, HIGH=3, EXTREME=4

HAZARDOUS INGREDIENTS

Isoparaffinic Naptha
Petroleum hydrocarbons

CAS

64741-65-7
64741-44-2

% WT

1-5
40-60

HAZARD DATA

LD50>8000 mg/kg (oral-rat)
LD50 >5 g/kg (oral-rat)

EXPOSURE LIMITS (TLV)

300 ppm
N/A

PHYSICAL DATA

Physical State: Wafer block

Odor/Appearance: Brown coloured,
pleasant odor

Boiling Point (C): N/D

Freezing Point (C): N/D

Solubility in Water: 0

Ph (undiluted): N/A

Evaporation Rate: N/D

Specific Gravity: N/D

Freeze/Thaw

Stable: Doesn't freeze

Percent Volatile (vol): 80

Vapor Pressure: N/D

FIRE & EXPLOSION HAZARD

Flammability: Y

Means of Extinction: Dry chemical, CO2, foam, water fog

Special Procedures: Dense smoke may be generated

Explosion Sensitivity to Impact: N/A

Chemical Sensitivity to Static Discharge: N/A

Flashpoint (C) & Method: N/D

Conditions:

Hazardous Combustion Products: CO, CO2

Upper Explosion Limit (% by vol): 6.0

Lower Explosion Limit (% by vol): 1.0

Auto-ignition: N/A

Rate of Burning: N/D

Explosive Power: N/A

TDG/WHMIS: Non hazardous / B4, D2B

REACTIVITY DATA

Chemical Stability: Stable

Hazardous Decomposition Product: None

Incompatible Substances: Strong oxidizing materials

TOXICOLOGICAL PROPERTIES

Route of Entry - Skin Contact: Y
Route of Entry - Skin Absorption: Y
Route of Entry - Eye Contact: Y
Route of Entry - Inhalation: N
Route of Entry - Ingestion: Y

Reproductive Effects Y/N: N
Carcinogenicity Y/N: N
Mutagenicity Y/N: N
Teratogenicity Y/N: N/D
TLV: N/D

Effects of Overexposure:

Acute Effects:

Harmful if swallowed. Will cause eye irritation on contact or through vapours.

Chronic Effects:

Prolonged skin contact may lead to dermatitis.

PREVENTATIVE MEASURES

Gloves: N/A
Eyes: N/A

Footwear: N/A
Respirator: N/A

Clothing: N/A
Other: N/A

Recommended Engineered Controls:
N/A

Leak & Spill Procedures:
Dispose of in waste receptacle.

Waste Disposal Methods:
According to federal, provincial and municipal regulations.

Special Handling Procedures:
Avoid excessive heat, open flames and all ignition sources.

FIRST AID MEASURES

Inhalation: Move person to fresh air. If necessary give artificial respiration or oxygen. Call a doctor if in distress.

Ingestion: Obtain medical attention immediately. Do not induce vomiting, as aspiration of material into lungs must be avoided.

Eye Contact: Immediately flush eyes with running water for at least 15 minutes. Contact a physician if irritation persists.

Skin Contact: Immediately flush skin for at least 15 minutes. Launder clothing before reuse. Contact a physician if irritation persists.

Prep./Revised Date: May 1, 2007

Prepared By: R. Russell

Source Material: Manufacturer's MSDS

Emergency Response: 1-613-996-6666 (Transport Emergencies)

Mailing Address: Esteam Manufacturing Ltd.
3750-19th Street NE Calgary, AB T2E 6V2



This information is complete to the best of our knowledge, however, users are encouraged to make their own investigations into the suitability of the information to their particular purposes. READ THE LABEL before using this or any product, and take any necessary precautions, dictated by the label or by common sense to ensure that your health is protected.