

eclean

DRY-SOLV

Dry-Solv is a volatile dry solvent for carpet and upholstery that evaporates quickly and completely. Dry-Solv works to remove oil, grease, tar and other oily spots and is the perfect first step in spotting an unknown stain as it will not set the stain.

pH: N/A

Packaged: 1 L & 4 L

Directions for use:

Do not mix this product with any other chemical product. Pretest in an inconspicuous location for color fastness.

Ready to use: Apply a small amount of Dry-Solv onto a clean white cloth and blot onto the soiled area. To agitate the area use a tamping brush. Blot with a clean white cloth working from the outside edges inward to prevent spreading of the spot or stain.



Distributed by:

SUPPLIER MATERIAL SAFETY DATA SHEET (MSDS) N/D=Not Determined N/A=Not Applicable

Product: Dry-Solv	Manufacturer: ESTEAM	Flammability: 1
Chem. Name: N/A	Trade Name: Volatile dry solvent	Reactivity: 0
Chem. Family: Chlorinated solvent	Use: spotting agent	Health: 2
		Protection:

NFPA LEAST=0, SLIGHT=1, MODERATE=2, HIGH=3, EXTREME=4

HAZARDOUS INGREDIENTS	CAS #	% WT	HAZARD DATA	EXPOSURE LIMITS (TLV)
Trichloroethylene	79-01-6	60-100	LD50 4920 mg/kg (oral-rat)	50 ppm TWA
Naptha (Petroleum) Heavy Alkylate	64741-65-7	10-30	LD50 >8000mg/kg (oral-rat)	N/A

PHYSICAL DATA				Freeze/Thaw
Physical State: Liquid	Boiling Point (C): N/D	Solubility in Water: N/D	Evaporation Rate: N/D	Stable: Doesn't freeze
Odor/ Appearance: Clear, light, solvent odour	Freezing Point (C): N/D	Ph (undiluted): N/A	Specific Gravity: N/D	Percent Volatile (vol): N/D
				Vapor Pressure: N/D

FIRE & EXPLOSION HAZARD		Conditions:
Flammability: N	Means of Extinction: Foam, CO2, Dry Chemical	Hazardous Combustion Products: N/D
Special Procedures: Do not use water.	Explosion Sensitivity to Impact: N/D	Upper Explosion Limit (% by vol): N/D
Chemical Sensitivity to Static Discharge: N/D	Flashpoint (C) & Method: None	Lower Explosion Limit (% by vol): N/D
		Auto-ignition: N/D
		Rate of Burning: N/D
		Explosive Power: N/D
		TDG/WHMIS: Trichloroethylene Class 6.1 UN 1710 PG III / D, D2B

REACTIVITY DATA	Chemical Stability:	Incompatible Substances:
Hazardous Decomposition Product: CO, CO2, smoke, Hydrogen Chloride, Phosgene (small amounts), Chlorine (small amounts)	Stable	Water, oxidizing materials

TOXICOLOGICAL PROPERTIES		Effects of Overexposure:
Route of Entry - Skin Contact: Y	Reproductive Effects Y/N: N/D	Acute Effects: May cause mild eye and skin irritation on contact. Inhalation may cause dizziness, drunkenness and drowsiness, unconsciousness and even death in extreme doses. Exposures in 1000 ppm range can cause narcosis.
Route of Entry - Skin Absorption: N	Carcinogenicity Y/N: N/D	Chronic Effects: Prolonged or repeated contact can cause dermatitis through defatting of the skin.
Route of Entry - Eye Contact: Y	Mutagenicity Y/N: N/D	
Route of Entry - Inhalation: Y	Teratogenicity Y/N: N/D	
Route of Entry - Ingestion: N	TLV: N/D	

PREVENTATIVE MEASURES	Gloves:	Footwear:	Clothing:
	Solvent resistant	N/A	N/A
	Eyes: Chemical goggles	Respirator: N/A	Other: Eye wash station

Recommended Engineered Controls:	Leak & Spill Procedures:	Waste Disposal Methods:	Special Handling Procedures:
Use with adequate ventilation. Local exhaust recommended.	Evacuate area, avoid vapours, contain spill. Mop or absorb material and collect to a closed container for disposal.	According to federal, provincial and municipal regulations.	Avoid skin contact, do not breath vapours. Store in a cool, dry, well ventilated area. Vapours will collect in low areas.

FIRST AID MEASURES
Inhalation: Move person to fresh air. If necessary give artificial respiration or oxygen. Call a doctor if in distress.
Ingestion: Do not induce vomiting. Contact a physician or poison centre immediately .
Eye Contact: Immediately flush eyes with running water for at least 15 minutes. Contact a physician if irritation persists.
Skin Contact: Immediately flush skin for at least 15 minutes. Launder clothing before reuse. Contact a physician if irritation persists.

Prep./Revised Date: January 8, 2010	Mailing Address: Esteam Manufacturing Ltd. 3750-19th Street NE Calgary, AB T2E 6V2
Prepared By: R. Russell	
Source Material: Manufacturer's MSDS	
Emergency Response: 1-613-996-6666 (Transport Emergencies)	



This information is complete to the best of our knowledge, however, users are encouraged to make their own investigations into the suitability of the information to their particular purposes. READ THE LABEL before using this or any product, and take any necessary precautions, dictated by the label or by common sense to ensure that your health is protected.