

# SUPPLIER MATERIAL SAFETY DATA SHEET (MSDS) N/D=Not Determined N/A=Not Applicable

**Product:** OLEFIN PRESPRAY

**Manufacturer:** ESTEAM

**Flammability:** 0

**Chem. Name:** N/A

**Trade Name:** Olefin Prespray

**Reactivity:** 0

**Chem. Family:** Mixture

**Use:** Olefin carpet preconditioner

**Health:** 2

**Protection:** 0

NFPA LEAST=0, SLIGHT=1, MODERATE=2, HIGH=3, EXTREME=4

## HAZARDOUS INGREDIENTS

2-Butoxyethanol  
N-Pentylacetate  
Coconut Diethanolamide

### CAS #

111-76-2  
62-86-37  
68603-42-9

### % WT

5-10  
1-5  
1-5

### HAZARD DATA

LD50 1746 mg/kg (oral-rat)  
LD50 6500 mg/kg (oral-rat)  
LD50 2700 mg/kg (oral-rat)

### EXPOSURE LIMITS (TLV)

25 ppm TWA  
150 ppm TWA  
N/D

## PHYSICAL DATA

**Physical State:** Liquid

**Odor/ Appearance:** Golden, candy odor

**Boiling Point (C):** 216 F

**Freezing Point (C):** N/D

**Solubility in Water:** Complete

**Ph (undiluted):** 11.3

**Evaporation Rate:** 1

**Specific Gravity:** Approx 1

### Freeze/Thaw

**Stable:** Yes

**Percent Volatile (vol):** 95+

**Vapor Pressure:** As water

## FIRE & EXPLOSION HAZARD

**Flammability:** N

**Means of Extinction:** N/A

**Special Procedures:** N/A

**Explosion Sensitivity to Impact:** N/A

**Chemical Sensitivity to Static Discharge:** N/A

**Flashpoint (C) & Method:** None

**Conditions:** N/A

**Hazardous Combustion Products:** N/A

**Upper Explosion Limit (% by vol):** N/A

**Lower Explosion Limit (% by vol):** N/A

**Auto-ignition:** None known

**Rate of Burning:** N/A

**Explosive Power:** N/A

**TDG/WHMIS:** Non hazardous / D2B

## REACTIVITY DATA

**Chemical Stability:** Stable

**Hazardous Decomposition Product:** Ammonia, CO, CO2

**Incompatible Substances:** Strong acids

## TOXICOLOGICAL PROPERTIES

**Route of Entry - Skin Contact:** Y  
**Route of Entry - Skin Absorption:** Y  
**Route of Entry - Eye Contact:** Y  
**Route of Entry - Inhalation:** N  
**Route of Entry - Ingestion:** Y

**Reproductive Effects Y/N:** N/D  
**Carcinogenicity Y/N:** N/D  
**Mutagenicity Y/N:** N/D  
**Teratogenicity Y/N:** N/D  
**TLV:** N/D

### Effects of Overexposure:

#### Acute Effects:

May cause eye and skin irritation. May be harmful if swallowed. Inhalation of fumes may cause irritation.

#### Chronic Effects:

Repeated or prolonged contact may cause defatting dermatitis.

## PREVENTATIVE MEASURES

**Gloves:** Rubber recommended

**Footwear:** N/A

**Clothing:** N/A

**Eyes:** Chemical Glasses

**Respirator:** N/A

**Other:** N/A

### Recommended Engineered Controls:

Use with adequate ventilation. Local exhaust recommended.

### Leak & Spill Procedures:

Mop up excess. Flush with water to a sanitary sewer.

### Waste Disposal Methods:

According to federal, provincial and municipal regulations.

### Special Handling Procedures:

Keep container tightly closed. Store in a cool, dry place away from children.

## FIRST AID MEASURES

**Inhalation:** Move person to fresh air. If necessary give artificial respiration or oxygen. Call a doctor if in distress.

**Ingestion:** Contact a physician.

**Eye Contact:** Immediately flush eyes with running water for at least 15 minutes. Contact a physician if irritation persists.

**Skin Contact:** Immediately flush skin for at least 15 minutes. Launder clothing before reuse. Contact a physician if irritation persists.

**Prep./Revised Date:** January 8, 2010

**Prepared By:** R. Russell

**Source Material:** Manufacturer's MSDS

**Emergency Response:** 1-613-996-6666 (Transport Emergencies)

**Mailing Address:** Esteam Manufacturing Ltd.  
3750-19th Street NE Calgary, AB T2E 6V2



This information is complete to the best of our knowledge, however, users are encouraged to make their own investigations into the suitability of the information to their particular purposes. READ THE LABEL before using this or any product, and take any necessary precautions, dictated by the label or by common sense to ensure that your health is protected.